

# SilverLine<sup>®</sup>-TT (TempTrack)

ISO 9001 Certified


## Coaxial Test Cables For:

- *RF Testing From 0°C to +30°C*
- *Phase Critical RF/Microwave Measurement*
- *Research and Development*

Now +125°C  
Operating Temperature  
on Both Armored and  
Unarmored Style!\*



SilverLine<sup>®</sup>-TT features solid TF-4<sup>™</sup> dielectric. This proprietary dielectric exhibits smaller and more linear phase change at normal ambient temperatures of 0° C to + 30° C, when compared to solid PTFE. Although somewhat improved phase performance can be achieved using foam, taped or spline dielectrics, ruggedness is sacrificed and the phase performance achieved is not as good as the SilverLine<sup>®</sup>-TT. The graph below compares solid PTFE to solid TF-4<sup>™</sup>.




## Time's Silverline<sup>®</sup> Product Guarantee

Times will repair or replace your SilverLine test cable at its option if the connector attachment fails within four months of shipment. This guarantee excludes cable or connector interface damage from misuse or abuse.

## Features & Benefits

- *Less and Linear Phase Change From 0° C to + 30° C*
- *Stainless Steel Connectors*
- *Ruggedized Cable/Connector Interface*
- *ROHS Compliant*

# SilverLine®-TT



## Cable Construction

**Inner Conductor:** Solid silver plated copper

**Dielectric:** Solid TF-4™

**Shield:** Silver-plated copper flat ribbon braid aluminum-polyimide tape interlayer 36 GA silver-plated copper round braid (90%k)

**Jacket:** Clear FEP

**Armor:** Optional

**Steel Style:** 100% coverage, square locked, galvanized steel hose, high angle steel braid and high temp TPR jacket

### Connectors

- Stainless steel construction
- SMA and Type N OneTurn™ options

\* SMA and Type N mating life assumes the use of a calibrated torque wrench, interfaces are clean and within mil spec limits.

\*\*See SilverLine-VNA data sheet for flex test conditions. A brand new cable can have a break-in period of several hundred flexes.

**A brand new cable can have a break-in period of several hundred flexes.**

*Specifications subject to change without notice.*

Mechanical Specifications		
Dimensions	in	mm
Outside Diameter	0.195	4.95
Armor (optional)	0.450	11.50
Minimum Bend Radius (unarmored)	1	25
Connector Retention	>175 lbs (unarmored) 300 lbs (armored)	
Crush Resistance (armored)	1500 lbs per linear inch	
Mating Life Cycle	>5000*	
Increased Temperature: *(serial# 32,000 & above)	unarmored or armored: -67°/+257°F 55°/+125°C	

Electrical Specifications			
VSWR Max		6 Ghz	18 Ghz
	SMA, Type N, TNC, Swept r/a	1.25:1	1.30:1
	SMA r/a, Type N, r/a	1.30:1	1.35:1
Impedance	50 Ohms		
Velocity of Propagation	70%		
Shielding Effectiveness	>100 dB		
Capacitance	29.0 pf/ft (95.1 pf/m)		
Phase Stability ** (50,000 cycles)	+/-2° through 18 GHz		
Phase change from 0° to + 30° C	35 ppm/deg C +/-10 ppm/deg C		
Attenuation, max @77°F (25°C)			
	Frequency (Ghz)	dB/100 ft	(dB/100 m)
	1	12	(40)
	2	18	(59)
	6	35	(115)
	12	53	(174)
	18	69	(226)

Cable Power Handling @77°F (25°C) sea level, watts, (max)	
Frequency Ghz	
1	444
2	304
6	163
12	108
18	86

### Ordering Information

U = unarmored  
SB = steel armor

**Cable Type**  
TT = Temp Track

**Maximum Frequency**  
06 = 6 Ghz  
18 = 18 Ghz

SW suffix: Swept Right Angle

**SLXXTTXX-XXXXXXXXXX-XX.XXX**

Feet 0.5 ft increments  
Meters 0.25m increments

F = Feet, M = Meters

**Connector Codes 2 or 3 Characters**

SM = SMA male  
SF = SMA female  
SMR = SMA right angle  
NM = Type N male  
NF = Type N female  
NMR = Type N right angle  
TM = TNC male  
TF = TNC female

First Connector

↓

Second Connector

World Headquarters: 358 Hall Avenue, Wallingford, CT 06492 • Tel: 203-949-8400, 1-800-867-2629 Fax: 203-949-8423

International Sales: +1 203 949 8503 • +1 800 867 2629

China Sales: TMC Building 4, No. 318 Yuanshan Road, Xinzhuang Industrial Park, Shanghai, China 201108 Tel: 86-21-5176-1209 Fax: 86-21-64424098

www.timesmicrowave.com

© 2015, Times Microwave Systems, Wallingford, CT 06492

SL-TT 03/16